

Dual Intel Xeon 1U Rackmount Server



MODEL		TSS 1520	
CPU		Dual Intel® XEON 2.4GHz or higher with 512K Cache	
Memory / HDD		Up to 4GB memory / 3xHDD	
Motherboard Features	CPU Support	Dual Intel® XEON	
	CPU Socket	Socket 604	
	FSB (Front Side Bus)	400/533 MHz	
	Chipset	Server Work GC-SL	
	Memory Type	Low Profile ECC Registered DDR266	
	ECC Support	YES	
	Max Memory	4GB	
	Memory Slots	DIMM x 4 (1 DIMM per Bank)	
	VGA	ATI® Rage XL	
	VGA Memory	8MB	
	SCSI Controller	Adaptec® AIC-7902W	
	RAID Support	ZCR Adaptec Raptor (SODIMM) support	
	Ethernet Support	Intel® 82545 (Gigabit) x 1 Intel® 82550 (100BaseT) x 1	
	PCI-X Full-height Slots	64-bit / 100MHz x 1	
	PCI-X Low-profile Slots	64-bit / 100MHz x 1	
Managementability	IPMI 1.0 (optional)		
Exterior Highlights	Form Factor	1U	
	Dimension	430W x 650D x 43H (mm)	
	3.5" Front Hot-swap Drive Support	Ultra 160,320 SCSI/SCA 80-Pin Disk	3
		ATA-133 Disk	-
		ATA-100 Disk	-
		Easy-swap ATA-100 for OS boot	-
	FDD	Slim x 1	
	CD-ROM	Slim x 1	
	Front USB/Serial Port(s)	-	
	Rear I/O Shield	2xPS2 / 2xUSB / 1xVGA / 2xCOM / 2xLAN / 1xWideSCSI	
LED Indicators	Power ON/Access/Service/Error		
Power Supply	350W		



436 Kato Ter. Fremont, CA 94539

Tel: (800)659-5902 (510) 687-9688 FAX: (510) 687-9588

URL: <http://www.tsti.com> Email: mkt@tsti.com

Features and Specifications include standard and optional items, and are subject to change without notice.

Intel® is the trademark of Intel Corp. All product names, trademarks and registered trademarks are the property of their respective owners.